

MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0502 18" CUT-OFF SAW (ALSO KNOWN AS A "JUMP SAW")

Product Dimensions:	
Weight	
Length/Width/Height	184-1/2 x 33-1/2 x 50-1/4 in
Foot Print (Length/Width)	182 x 27 in
Shipping Dimensions:	
Carton #1	
Туре	Wood Slat Crate
Content	Machine
9	
Length/Width/Height	31 x 31 x 52 in.
Carton #2	
Type	Wood Slat Crate
Content	Extension Rollers
Weight	
Length/Width/Height	
Electrical:	
	Magnetic with Thermal Overload Protector
Switch Voltage	220V
Minimum Circuit Size	
Plug Included	No
	P0502144
Phase Converter	G7978
Motors:	
Main	
Type	TEFC Induction
	10 HP
•	220/440V
	220V
Phase	Three
Amps	25/12.5A
·	3450 RPM
	60 Hz
•	Belt Drive
	Shielded and Lubricated
Main On selfications	
Main Specifications:	
Operation Information	
	1 in.
	3600 RPM
Max Cut Cycle Speed	81 SPM

Cutting Capacities	
Max Cut Cap Height	2, 3, 4 in.
Max Cut Thickness	2, 3, 4 in.
Max Cut Cap Width	12, 11, 10 in.
Max Cut Length	78 in.
Min Cut Length	12 in.
Table Information	
Floor To Table Height	
Table Size Length	
Table Size Width	27 in.
Table Size Thickness	
Ext Rollers Size	78 in.
Overall Width With Ext Rollers	
Overall Width Without Ext Rollers	
Fence Information	
Fence Type	Cast Iron
Fence Size Length	
Fence Size Width	1-7/8 in.
Fence Size Height	2 in.
Fence Stops	2
Construction Materials	
Table Construction	Precision Ground Cast Iron
Body Assembly Construction	Steel
Cabinet Construction	Steel
Rollers Construction	Pre-Formed Steel
Fence Assembly Construction	Precision Ground Cast Iron
Rails Construction	Steel
Guard Construction	Steel
Spindle Bearing Type	Sealed and Lubricated for Life
Paint	Ероху
Other Related Information	
No Of Dust Ports	1
Dust Port Size	4 in.
Other Specifications:	
Country Of Origin	Taiwan
•	
Warranty	
Serial Number Location	
Assembly Time	1 hour

Features:

Model G0502

78" Infeed and 78" Outfeed Roller Extension Adjustable Swing Stop Controls Blade Travel Automatic Safety Guard Convenient Cycle Speed Adjustment Easily Adjustable Clamp **Emergency Button for Cutting Release** Foot Switch Start Fully Enclosed Blade Guard Heavy Duty Fixed Work Stop and Flip Stop Quick Stop Connect Fitting